



Dry Floors, Circulate & Exhaust Air

The HAWK Industrial Air Mover with 1/2 HP, 3-speed industrial motor moves air up to 2950 CFM. Built with super-tough polypropylene housing for long-term use in construction, manufacturing and housekeeping. The metal cage mounted on the housing adds discharge safety.



Moves Air at 3 Angles

Power

- 0.5 HP, 3-speed motor
- 115 V, 50/60 HZ power. 230V available.
- 35 ft., 2-part, (16-3) SJTOW power cord with molded plug
- Top-mounted quick change 3-speed switch

Engineered Design

- Three air flow speeds - 2000, 2500 and 2950 CFM. Moves up to 50 ft. at high speed.
- Speed switch is conveniently located next to lifting handle
- Continuous-duty rugged ball bearing motor
- Roto-molded polyethylene housing with lifetime warranty
- Plastic fan wheel
- Steel handle and discharge guard
- 8 rubber feet for non-slip positioning
- Stackable for easy storage
- Convenient size - 19.5" x 14.5" x 18.25"

Safety features

- Quiet operation with dB sound levels: Low speed 59 , Medium 62, High speed 64. Meets GS42 standard.
- UL -listed.



Specifications

Model	BH001		
Part Number	BH001-02 (BLK), BH001-08 (BLU)		
Motor	0.5 HP, 3-Speed 110V motor		
Motor CFM	2950 CFM	2500 CFM	2000 CFM
Amp Draw	5.3 Amp	4.5 Amp	4.3 Amp
Power Cord	35 ft., 2-Part, (16-3) SJTOW Power Cord		
Housing	Roto-Molded Machine Housing		
Positions	Directs Air at 0, 45 and 90 Degrees		
dB Rating	59 dB (low speed), 62 dB (medium), 64 dB (high) Meets GS42 Standards		
Machine Size	19.5" x 14.5" x 18.25"		
Ship Size	20" x 20" x 20"		
Weight	31 lbs.		

Subject to Change Without Notice



Moves Air Up to 60 ft. at High Speed



Compact Power 19.5" x 14.5" x 18.25"



Metal Carrying Handle